







PCB LAYOUT
(Top View)



SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.

Contact Resistance : 20milli-Ohm Max.

Rating Current : 1.5A Max.

Rating Voltage : 120V AC.

Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

Housing : PBT Glass Filled (UL 94V-0)

Color : Black Color

Spring Wire : 0.45mm Dia. Phosphor bronze
Gold Plating Over Nickel

Temperature Range : - 25 /+90 Deg C

Durability : 500 Mating cycles Min.

HC-019-6-X-X

B=6p2c, C=6p4c
D=6p6c

Gold plated
1=15u , 3=50u
2=30u , 4=6u

HO CHIEN

www.hochien.com

TITLE

VERY LOW PROFILE SIDE ENTRY PCB JACK
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-019-6-X-X

SCALE SIZE DWG. NO. 9695 SERIES

DWG. NO.

AS019002

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
THIRD ANGLE PROJECTION	LINEAR	MM INCH	00±0.01 000±0.005 0000±0.002	00±0.25 000±0.13 0000±0.05	CK'D Steven Johnn APP'D Billy
MM INCH	ANGLE ±0°30'	RADIL	+0.45 -0.15		JAN-12 '05 JAN-12 '05 JAN-12 '05